DE CHENG Page 1 of 3

DE CHENG		
ТҮРЕ		
Classification	CCS	
Flag	P.R. China	
Port of Registr	Yantai	
Builder	GDANSK Shipyard	
Year Built	1983	
Call Sign	BSJE	
Trade Area	1 (Unlimited)	
Registered Number	8000393	
MANINI DICAMENICEC		
MAIN DISMENSES	81.30 m	
Length Overall		
Length on Load Waterline Breadth Molded	71.45 m	
	16.30 m	
Depth Molded	7.20 m	
Full Load Draft	4.90 m	
Freeboard	2.30 m	
TONNAGE		
Full Load Displacement	4009.80 T	
Light Displacement	2631.20 T	
Gross Tonnage	2737.00 T	
Net Tonnage	821.00 T	
Deadweight	1000.00 T	
DECK CAPACITIES		
Deck Area	385.00 m ² (35 m x 11 m)	
Protective Handrail (High)	1.50 m	
Deck Cargo	800.00 T	
Deck Strength	5.00 T/m ²	
DECK EQUIDMENT		
DECK EQUIPMENT Anchor	2 x 2.46 T	
Anchor Chain	2 x L 605 m x D 40 mm	
Windless	20 m/min	
Capstan	5.00 T	
Derrick Boom	12.00 T	
Defrick boom	12.00 1	
CARGO CAPACITIES		
Bulk Cargo	46.40 x 4 m ³	
Potable Water	550 m ³	
Drill Water	500 m ³	
Ship Fuel	640 m ³	
Jack Up Fuel Oil	300 m ³	
	35 m ³	
Lube Oil	30 III-	

DE CHENG Page 2 of 3

TRANSFER RATES	
Bulk Cargo	20 m ³ /Partial Pressure 0.8 MP
Potable Water	63 m ³ /hr
Drill Water	275 m ³ /hr
Fuel Oil	68.8 m ³ /hr
i dei oli	00.0 111 7111
MACHINERY	
Main Engine	62L40/49
Horse Power	2 x 2650 KW
Bollard Pull	78.50 T
Propeller	2 Controllable Pitch Propellers
Auxiliary Engine	3 x 6AL 20/24-426 KW
Generator	3 x GD8-500-50/04-384 KW
Bow Thruster	6AL 20/24-426 KW
Control System	Electric-Pneumatic Control
CONSUMPTION	A L WT
Cruising Speed	14 KT
Economic Speed	10 KT
Range	7200 Sea Mile
NAVIGATION/COMMUNICATION	
Gyro Compass	ВЕРА
Magnetic Compass	Mirror Tube Reflector
Auto Pilot	MS125-1-S'/1
ECHO COUNDED	
ECHO SOUNDER Radar	Furunom-1510D
Goniometer	
Weather Facsimile	PYMS Fax-207
	GP-50Mark-2
Satellite Navigator	1C-M700TY
Single Side Band Communication Receiver	CNBNP6
VHF	2 x Motorola
Portable VHF	HX2205 (6 W/1 W)
rortable viir	TAZZUS (U W/ I W)
SAFETY EQUIPMENT	
Lifebuoy	12
Lifejacket	41
Lifecraft	Inflatable, 10 persons x 4
Lifeboat	2 totally enclosed
Fire-Fighting Appliance	5 sets Main Fire Pumps
	Capacity: 160 m ³ /hr, 65 m High delivery lift
Prevention of Pollution	Oily-water separating equipment
TOWANG ANGLIOD	
TOWING ANCHOR	1500 KM Tauring Mins D. U
Towing Winch	1500 KN Towing Wire Pull

DE CHENG Page 3 of 3

Towing Wire	L 1000 m x DD 60 mm
Anchor Wire	L 1000 m x DD 60 mm
Short Rope	L 30 m x D 56 mm x 4
Shackle	35 T - 85 T
Pennant Wire/Chain Stopper	Double Towing Pins
Short Nylon Wire/Rope	2 x 8 inches
Stern Drum	1
PROVISION RESERVE	
Freezing Room	6 m ² (-10°C)
Refrigration Room	80 m ² (+4°C)
CONNECTION	
Bulk Cargo Hose	5" joint
Water-Carrying Hose	4" joint
Water-Carrying Hose	4" joint